

Technical Data Sheet
Product: GLITTER PAINT
Reference: GP-SE-GLT

Description

Glitter Paint – Infill Colour Pigments are a combination of Acrylic and Epoxy transparent resins with exceptional properties. These pigments are designed to be mixed into supreme Base & Hardener and can be applied onto all types of glass including Toughened / Tempered Glass. The products are industrial grade and are chemically curing. They are non-isocyanate. There are 4 Glitter Infill Paint colours (Gold, Silver, Copper and Rainbow). The product is UV stable and weather resistant.

Recommended Substrates

Glass, Toughened / Tempered Glass. Laminated Glass

Features and Benefits

4 glitter coloured pigment | High gloss surface | Excellent Surface Adhesion | UV stable and weather resistant | Excellent scratch resistance | 10 year external warranty | Suitable for use within double and triple glazed sealed units | Resistant to high temperature | Water resistant | Good chemical resistance

Mixing and Application

Cleaning: Clean all types of glass thoroughly using Creative Resins non filming glass cleaner. Hand Application: Mix Supreme Base and Supreme Hardener together in equal amounts and add a small amount of Glitter Infill Paint. Stir well and allow one or two minutes for the air bubbles to disperse. Apply using a conventional spray gun.

Chemical Properties

Acrylic and Epoxy Solids content: +55% Colour: Glitter

Product viscosity: 34sec ± 1-5sec using Ford 4 Cup.

Touch dry at 20°C: 25 minutes Total dry at 20°C: 24-36 hours Full

cure: 7days Sizes: 125ml

Unit 17C, Upper Field Road, Sittingbourne, Kent, ME10 3UP UK



info@creative-resins.co.uk



www.creative-resins.co.uk



00 44 (0) 1795 411 820

