



Description

Granite Infill Pigments are a combination of Acrylic and Epoxy transparent resins with exceptional properties. These pigments are designed to be mixed into Clear Colour Base & Hardener and applied by hand using an application bottle or pipette onto all types of glass including Toughened / Tempered Glass. The products are industrial grade and are chemically curing. They are non-isocyanate. The Granite Infill Pigment is available in black and white and can be inter mixed. The product is UV stable and weather resistant.

Recommended Substrates

Glass, Toughened / Tempered Glass. Laminated Glass

Features and Benefits

2 Colours, Black and White | High gloss surface | Excellent Surface Adhesion | UV stable and weather resistant | Excellent scratch resistance | 10 year external warranty | Suitable for use within double and triple glazed sealed units | Resistant to high temperature | Water resistant | Good chemical resistance

Mixing and Application

Cleaning: Clean the glass thoroughly using Creative Resins non filming glass cleaner. For application onto Satin or Acid etched glass clean using Creative Resins glass cleaner.

Hand Application: Mix Clear Colour Base and Clear Colour Hardener together in equal amounts and add a small amount of the Granite Effect Paint infill resin. Stir well and allow one or two minutes for the air bubbles to disperse. Apply using an application bottle or pipette. Can also be applied to large areas using a conventional spray-gun. Keep the product agitated while it is being applied for even coverage.

Chemical Properties

Product Material: Acrylic and Epoxy

Solids Content: +55%

Colour: Black and White

Product Viscosity: 24sec \pm 1-5sec using Ford 4

Touch dry at 20°C: 25 minutes

Total dry at 20°C: 24-36 hours

Unit 17C, Upper Field Road, Sittingbourne, Kent, ME10 3UP UK

✉ info@creative-resins.co.uk

🌐 www.creative-resins.co.uk

☎ 00 44 (0) 1795 411 820



