



## Description

Plaspaint H20 Pre-mixed is also available for PVC and other hard plastics such as ABS, polycarbonate, and acrylic as well as polyester powder coatings. PlasPaint H20 paint spray is simple and fast to apply. excellent water repellent properties UV stable and weatherproof

## Recommended Substrates

composite, steel, aluminium, PVCu

## Features and Benefits

Excellent Surface Adhesion | UV stable and weather resistant | Excellent scratch resistance  
Excellent chemical resistance | Can be machined after cure | Available in Gloss, Satin and Matt | Available in any colour | Fast drying

## Mixing and Application

Mix: Premixed to any colour and ready to use. Add 2% adhesion solution prior to use. Stir thoroughly apply paint using gravity fed spray gun or automatic spray machinery.

All substrates must be prepared using CR degreaser or foil safe degreaser.

For PVCu use a fine scouring pad dipped in water and lightly rub the surface of the white profile creating a very fine surface key. Wipe dry with a soft tissue and then using a soft cloth wipe the surface clean using CR degreaser before applying Plaspaint H20.

## Chemical Properties

Product density: 1,01 g/cm<sup>3</sup> ± 0,010 at 20oC  
Colour: Transparent  
Product viscosity: 35sec ± 3sec FORD 4 Cup  
Application viscosity: 35sec ± 3sec FORD 4 Cup

Touch dry at 20oC: 30 minutes  
Total dry at 20oC: 6 hours  
Full cure: 7 days

Unit 17C, Upper Field Road, Sittingbourne, Kent, ME10 3UP UK

✉ info@creative-resins.co.uk

🌐 www.creative-resins.co.uk

☎ 00 44 (0) 1795 411 820



