



Description

PlasPaint Brush n Roll is a highly versatile Polyurethane Acrylic formulation. It is a combined primer and topcoat paint specifically formulated to provide outstanding performance on a variety of substrates. This single component paint is extremely economical as there is no waste. What is not used can be returned to the tin to be used in the future.

Recommended Substrates

It can be applied directly onto Fibreglass (GRP), Rigid Plastics (ASA, ABS), UPVc (PVCu), Steel and Aluminium.

Features and Benefits

Excellent Surface Adhesion | UV stable and weather resistant | Excellent scratch resistancy
Excellent chemical resistancy | Spray, brush or roller application

Mixing and Application

Available in any colour from our 'Colour Match' software ready to us from the tin. No need to dilute for brush and roller applications. Apply a first light layer, followed by a thicker layer. Once dry lighter colours may require a further coat.

Clean substrate with CR Degreaser prior to paint.

Chemical Properties

Density: 1,05 grs/cm³ ± 0.010 at 20°C
Colour: Any colour from 'Colour Match'
Solid contents: 45 % ± 5
Product viscosity: 243 " ± 15 FORD 4
Applycation viscosity: 30 " ± 5 FORD 4

Pot life: Infinite
Gloss: 15° ± 5
Dry at 20° C: Touch: 20 minutes
Total: 40 minutes
Re coat: 1 hour

Unit 17C, Upper Field Road, Sittingbourne, Kent, ME10 3UP UK

✉ info@creative-resins.co.uk

🌐 www.creative-resins.co.uk

☎ 00 44 (0) 1795 411 820



