



Description

Texture Solution gives the surface a unique matt look and touch similar to very fine wet and dry paper. PlasPaint Texture is pre-mixed to any colour and ready to use. Just add catalyst. It is an industrial quality highly versatile Polyurethane Acrylic paint specifically formulated to provide outstanding performance on a variety of substrates. It can be applied directly onto Fibreglass (GRP), Rigid Plastics such as ASA, ABS as well as UPVc (PVCu), Steel and Aluminium.

Recommended Substrates

directly onto Fibreglass (GRP), Rigid Plastics such as ASA, ABS as well as UPVc (PVCu), Steel and Aluminium.

Features and Benefits

Excellent Surface Adhesion | UV stable and weather resistant | Excellent scratch resistance
Excellent chemical resistance | Can be machined after cure | Fine surface texture | Available in any colour | Available in Matt or Gloss | Available in 1Ltr and 2.5Ltr tins

Mixing and Application

Mix: Add Catalyst at 20%. Stir thoroughly
Apply material using gravity fed spray gun or automatic spray machinery.
All substrates must be prepared using CR degreaser or foil safe degreaser.
For PVCu use a fine scouring pad dipped in water and lightly rub the surface of the white profile creating a very fine surface key. Wipe dry with a soft tissue and then using a soft cloth wipe the surface clean using CR degreaser before applying PlasPaint Texture.

Chemical Properties

Product density: 1,01 g/cm³ ± 0,010 at 20oC
Colour: Transparent
Product viscosity: 40" ± 3" Cup: FORD 4
Application viscosity: 25" ± 5" Cup: FORD 4

Touch dry at 20oC: 30 minutes
Total dry at 20oC: 6 hours
Mixture Pot-life: 4 hours

Unit 17C, Upper Field Road, Sittingbourne, Kent, ME10 3UP UK

✉ info@creative-resins.co.uk

🌐 www.creative-resins.co.uk

☎ 00 44 (0) 1795 411 820



