

Technical Data Sheet

Product: PLASPAINT GRAINEX STAIN

Reference: **PP-GNX**

Description

PlasPaint Grainex stain is designed to simply wipe-on (or spray-on) and it immediately enhances the wood grain creating a stand out effect. It is pre-mixed to enhance the natural grain colours and works hand in hand with the GrainEx base coat. GrainEx Stain / Patina has excellent surface adhesion, is UV stable and weatherproof. It is completely water-based and VOC-free. The solution is used in conjunction with the matching PlasPaint base wood colour and finally sealed with the PlasPaint Protective coat. GrainEx stain is also suitable for PVC and other hard plastics such as ABS, polycarbonate and acrylic. It is simple and fast to apply either by conventional spray gun or by hand using the sponge head bottle. It has excellent water repellent properties as well as being UV stable and weatherproof.

Recommended Substrates

Composite, UPVc (PVCu)

Features and Benefits

Excellent Surface Adhesion | UV stable and weather resistant | Excellent scratch resistance Excellent chemical resistance | Can be machined after cure | Available in the most popular wood grain and foil colours | Available in 500ml and 1Ltr sizes

Mixing and Application

Mix: ready to use. Stir thoroughly for spraygun application or shake well if using sponge head bottle.

Apply material using gravity fed spray gun or wipe on and off manually.

All substrates must be prepared using CR degreaser or foil safe degreaser.

Must be applied on top of PlasPaint GrainEx base and sealed using PlasPaint GrainEx topcoat.

Chemical Properties

VOC Water based acrylic polymer

Colour: Various

Touch dry at 20oC: 10minutes Total dry at 20oC: 1 hours

Unit 17C, Upper Field Road, Sittingbourne, Kent, ME10 3UP UK



info@creative-resins.co.uk



www.creative-resins.co.uk



00 44 (0) 1795 411 820

