

Technical Data Sheet Product: MIRROR 1K Reference: GP-SE-MIR

Description

High reflective paint for glass replicating real mirror. Easy to apply using a conventional spray gun and fast drying. Works on any type of glass including toughened and can be used to create a number of Antique Mirror effects. Back with CR GlassPaints Supreme to protect the mirror.

Recommended Substrates

Any type of glass including toughened.

Features and Benefits

Excellent Adhesion to Glass | Fast Drying | High Reflectivity | Heat Resistant

Mixing and Application

- 1. Clean the class thoroughly with CR Glass Cleaner.
- 2. Heat glass in heated booth or with heat gun.
- 3. Shake tin well and pour directly in to gravity fed spray gun.
- 4. Apply Mirror 1K using high pressure (approx. 3bar) and low volume.
- 5. After 1 hour, spray backing / protective coat of GlassPaints A and B, grey or black in colour.
- 6. Allow to fully cure over night before installation.

Chemical Properties

Product density: $0.870 \text{ grs} / \text{cm}3 \pm 0.001$ Gloss: $90^{\circ} \pm 10$

Colour: Silver Touch dry at 20°C: 10 minutes

Product viscosity: 8"± 1" Cup: FORD 4 Total dry at 20°C: 1 hour

Application viscosity: 8"± 1" Cup: FORD 4 Recoat: 1 hour

Unit 17C, Upper Field Road, Sittingbourne, Kent, ME10 3UP UK



info@creative-resins.co.uk



www.creative-resins.co.uk



00 44 (0) 1795 411 820

