Description

GlassPaint H20 is a specially prepared Acrylic crosslinking copolymer that has an exceptional adhesion directly onto all types of glass including toughened glass. It can also be used on ceramic tiles. GlassPaint H20 has excellent water repellent, alkali resistant, UV stable and weatherproof properties, and can also be used internally and externally.

It is fast drying and easy to apply using a conventional spray gun. It has excellent heat resistance, making it ideal to use directly behind hobs and ovens in kitchen areas or externally in direct sunlight.

GlassPaint H20 can be pigmented using Creative Resins concentrate WB colour pigments and the Colour Match software to provide an infinite range of colours including RAL, NCS, Pantone and numerous other corporate colours. The product is water-based, VOC free, odour-less and a perfect blackout paint for glass.

Recommended Substrates

Glass, Toughened / Tempered Glass. Laminated Glass

Features and Benefits

Excellent Surface Adhesion | UV stable and weather resistant | Excellent scratch resistancy
Excellent chemical resistance | Suitable for domestic, commercial and industrial application
Transparent, Transluscent and Opaque colours | High Gloss finish

Mixing and Application

Cleaning: Clean the glass thoroughly with CR Glass Cleaner.
Mixing: Glasspaint H2O Premixed is designed to be ready to use with the addition of 1-2% Adhesion. GlassPaint H2O base is manufactured clear for 10% pigment and 1-2% Adhesion to be added.
Automatic application: Spray Master, Picasso. **Hand Application:** Using a conventional spray gun.

Chemical Properties

Product Material: Polymer
Colour: Transparent / Premixed (Any Colour)
Product viscosity: 40 - 1,000 mPas

Touch dry at 20ºC: 10-15 minutes
Total dry at 20ºC: 1-2 hours
Full Cure: Up to 7 days