



Description

Crackle is a unique system where the base coat fractures in an irregular fashion leaving a transparent vein. A topcoat is then applied that can be transparent, coloured or even mirror that fills the clear vein areas creating stunning and unusual effects. GlassPaint H2O Crackle is a specially prepared Acrylic crosslinking copolymer that has an exceptional adhesion directly onto all types of glass including toughened glass. It can also be used on ceramic tiles. GlassPaint H2O Crackle has excellent water repellent properties, is alkali resistant, UV stable and weatherproof. It can also be used internally and externally.

It is fast drying and easy to apply using a conventional spray gun. It has excellent heat resistance, making it ideal to use directly behind hobs and ovens in kitchen areas or externally in direct sunlight.

GlassPaint H2O Crackle can be pigmented using Creative Resins concentrate WB colour pigments and the Colour Match software to provide an infinite range of colours including RAL, NCS, Pantone and numerous other corporate charts. The product is water-based, VOC free and odour-less.

Recommended Substrates

Glass, Toughened / Tempered Glass. Laminated Glass

Features and Benefits

Excellent Surface Adhesion | UV stable and weather resistant | Excellent scratch resistance | Excellent chemical resistance | Suitable for domestic, commercial and industrial application | High Gloss finish

Mixing and Application

Cleaning: Clean the glass thoroughly with CR Glass Cleaner.

Mixing: Glasspaint H2O Crackle is supplied ready to use with the addition of 1-2% Adhesion.(supplied) GlassPaint H2O Crackle base is manufactured clear. Add 10% WB pigment and 1-2% Adhesion and mix well.

Hand Application: Using a conventional spray gun.

Chemical Properties

Product Material: Polymer

Colour: Transparent /

Premixed (Any Colour)

Product viscosity: 30Sec

Ford 4 Cup

Touch dry at 20oC: 10-15
minutes

Total dry at 20oC: 1-2
hours

Full Cure: Up to 7 days

Unit 17C, Upper Field Road, Sittingbourne, Kent, ME10 3UP UK

✉ info@creative-resins.co.uk

🌐 www.creative-resins.co.uk

☎ 00 44 (0) 1795 411 820



