



Description

Glasspaint Pre-mixed is a combination of Acrylic and Epoxy transparent resins with high durability properties. They are designed to be mixed together in equal proportions and applied by conventional spray equipment onto a variety of substrates including all types of Glass, Toughened / Tempered Glass. The products are industrial grade and are chemically curing. They are non-isocyanate. They can be spray applied onto the surface of glass to create long term weatherproof and UV stable colours. They achieve excellent scratch and chemical resistance and provide a permanent bond to the substrate surface, especially glass. GlassPaint Supreme A and B form a transparent base solution. Creative Resins UT pigments are added to formulate any colour and can be in a transparent, translucent or opaque finish. It can be used internally or externally and is heat and water repellent.

Recommended Substrates

Glass, Toughened / Tempered Glass. Laminated Glass

Features and Benefits

Excellent Surface Adhesion | UV stable and weather resistant | Excellent scratch resistance | Excellent chemical resistance | Suitable for domestic, commercial and industrial application | Pearlescent base colour | High Gloss finish.

Mixing and Application

Cleaning: Clean the glass thoroughly with CR Glass Cleaner.

Mix your pre mixed colour in equal amounts.

Allow time for the mixture to de-air before using.

Automatic application: Spray Master, Picasso, curtain coater

Chemical Properties

Product Material: Acrylic and

Epoxy Colour: Transparent/
premixed (Any Colour)

Product viscosity: 243" \pm 1-5" Cup

Cup: FORD 4

Solids content: +55%

Touch dry at 20°C:

10 minutes

Total dry at 20°C: 1

hour

Full Cure: 7 days

Unit 17C, Upper Field Road, Sittingbourne, Kent, ME10 3UP UK

✉ info@creative-resins.co.uk

🌐 www.creative-resins.co.uk

☎ 00 44 (0) 1795 411 820



