



## Description

Two component (2K) Epoxy Primer in RAL 7032 Grey is a high performance anti-corrosion paint for steel, galvanised steel, stainless steel, zinc and aluminium. Exceptionally versatile this Industrial quality primer is perfect for internal and external areas that demand high mechanical, chemical and abrasion resistance. It provides exceptional adhesion directly onto metal and delivers high antioxidant and anti-corrosive protection.

## Recommended Substrates

Steel, stainless steel, galvanised steel, zinc and aluminium.

## Features and Benefits

Excellent Surface Adhesion | Excellent mechanical, chemical and abrasion resistance | High Antioxidant and anti-corrosive properties

## Mixing and Application

**Cleaning:** Degrease substrate using CR degreaser. Remove all rust and corrosion.

**Mixing:** Mix Epoxy Primer 7011 with 20% Catalyst.

**Application:** Spray gun - Dilute with CR reducer if required to achieve desired viscosity for spray gun application. Brush and roller - Direct application. It does not need to be diluted.

Apply 2 coats of Epoxy Primer 7011. Recoat after 120minutes (at 20° C)

Apply appropriate CR polyurethane top-coat.

## Chemical Properties

Product density: 1,15 gr/cm<sup>3</sup> ± a t 20°C

Colour: GREY RAL 7032

Product viscosity: 34sec ± 5sec Cup: FORD 4

Application viscosity: 34sec ± 5sec Cup: FORD 4

Unit 17C, Upper Field Road, Sittingbourne, Kent, ME10 3UP UK

✉ [info@creative-resins.co.uk](mailto:info@creative-resins.co.uk)

🌐 [www.creative-resins.co.uk](http://www.creative-resins.co.uk)

☎ 00 44 (0) 1795 411 820

