

Technical Data Sheet

Product: 2K ANTI SLIP FLOOR PAINT

Reference: FP-ANTISL

Description

Creative Resins brings to you the perfect non-slip floor paint for stairs, wet rooms, swimming pools, paths and driveways and other areas prone to water saturation, making it an ideal floor paint for floors with hazardous demands. The anti-slip floor paint can also work for garage and other exterior floor areas where slippage is possible. This non-slip paint is a specially prepared Acrylic Polyurethane 2K system. It achieves C3 compliance with UNE-EN 12633. It is very hard and resilient and can withstand heavy footfall. This Non-Slip floor paint has excellent water repellent properties as well as being alkali resistant, UV stable, and weatherproof and can be used internally and externally. It has a textured finish. The anti-slip paint can be supplied ready to use in any colour. It can also be pigmented in house using Creative Resins UT colour pigments and the Colour Match software.

Recommended Substrates

Exterior and Interior Concrete, Concrete Slab, Garage and Driveway, Masonry, Brickwork.

Features and Benefits

Excellent Surface Adhesion | UV stable and weather resistant | Excellent scratch resistance | Excellent chemical resistance | Suitable for domestic, commercial and industrial application | Can be formulated to any colour | Available in Matt and Gloss finish | Anti Slip C3 compliant

Mixing and Application

Cleaning: Brush the surface of the substrate to remove any excess dust and debris including any old flaking paint. Make sure the surface to be painted is dry. Green concrete (freshly poured concrete) should be left to cure fully before painting. The first coat can be diluted using the appropriate CR thinner. Subsequent coats should be applied without diluting.

Mixing: Anti Slip Floor paint is cured using 25% catalyst by weight. CR UT Pigment ratio is 14/15%. Hand Application: Using a conventional spray gun, Paint Brush or Paint Roller

Chemical Properties

Product Material: Acrylic Polyurethane Touch dry 20C: 4 hours / Re-coat 20C: 8 hours

Colour: Translucent / Premixed (Any Colour) Full Cure: Up to 7 days

Product viscosity: 12 Sec / Ford 8 Cup Gloss levels: Matt 10 / Gloss 87

Unit 17C, Upper Field Road, Sittingbourne, Kent, ME10 3UP UK



info@creative-resins.co.uk



www.creative-resins.co.uk



00 44 (0) 1795 411 820

