

Technical Data Sheet
Product: SANDBLAST
Reference: GP-SE-SAND

Description

Sandblast effect paint is a 2 component pre-mixed paint that is easily applied using a conventional spray gun and dries to a fine texture finish with the look and feel of real sandblast glass. They are ideal for use on splashbacks and kitchen or bathroom glass surfaces. It is combination of Acrylic and Polyurethane transparent resins with high durability properties. They are designed to be applied by conventional spray equipment onto a variety of substrates especially Glass including Toughened / Tempered Glass. The products are industrial grade and are chemically curing. Achieving excellent scratch and chemical resistance and provide a permanent bond to the substrate surface, especially glass. It is supplied in a translucent finish. They can also be tinted to any colour using CR UT pigments. It can be used internally and externally and is heat and water repellent.

Recommended Substrates

Any glass - toughened, float or safety glass.

Features and Benefits

Excellent Surface Adhesion | UV stable and weather resistant | Excellent scratch resistance | Excellent chemical resistance | Suitable for domestic, commercial and industrial application | Translucent and Opaque finishes | High Gloss finish | Can be tinted to any colour

Mixing and Application

Preperation: Clean the glass thoroughly using CR solvent based glass cleaner. **Mixing:** Mix the Sandblast A and Sandblast B together at 1:1 ration. Stir thoroughly.

Automatic application: Spray Master, Picasso. **Hand Application:** Conventional spray gun.

Chemical Properties

Product Material: Acrylic and Epoxy

Touch dry at 20°C: 10 minutes

Colour: Translucent Total dry at 20°C: 1 hour

Product viscosity: 24sec ± 1¬5sec Cup: FORD 4 Full Cure: 7 days

Solids content: +55%

Unit 17C, Upper Field Road, Sittingbourne, Kent, ME10 3UP UK











00 44 (0) 1795 411 820

