



Description

Timber Decking Paint is a specially prepared Acrylic crosslinking copolymer that is fast drying and has an exceptional adhesion directly onto all types of wood. It is very resilient and can withstand heavy footfall. It creates a hard wearing polymer coating on the surface which is flexible, allowing expansion and contraction in extreme conditions.

Recommended Substrates

Wood decking, Wood garden furniture

Features and Benefits

Excellent Surface Adhesion | Scratch resistant | Good weathering properties | Very Fast drying
Spray Gun application | Brush application | Roller application | Very low VOC content

Mixing and Application

Stir thoroughly before use. Final colour will depend upon wood type, previous treatment and the number of coats applied. Apply 2 coats evenly along the grain. When applying subsequent coats, allow each coat to dry fully before recoating. Avoid heavy wear and tear for 48 hours after application. On previously stained decking, touch up bare areas and allow to dry before finishing with further coats. Do not apply in temperatures below 5C, in damp conditions or if rain is likely before the product has dried.

Chemical Properties

Coverage: 10-12m² per 1Ltr
Touch dry at 20°C: 60-80 minutes
Total dry at 20°C: 4-6 hours
Full cure: 48 hours

Unit 17C, Upper Field Road, Sittingbourne, Kent, ME10 3UP UK

✉ info@creative-resins.co.uk

🌐 www.creative-resins.co.uk

☎ 00 44 (0) 1795 411 820

